

# Fame

**The Reference for Customization**

© 2000-2014 by Piotr Bednaruk  
All Rights Reserved

## Introduction

Do you know one single man who has ever read an introduction to some reference? Neither do I. So please just hit Page Down.

## Configuring Notepad++

It is very convenient to have a dedicated text editor with syntax highlighting and other cool stuff to create and maintain scripts. One example of such an editor is Notepad++. Its quite fast, stable and full of useful features. Fame comes with a set of syntax highlighting files especially for Notepad++, so that you receive:

- syntax coloring
- code completion and parameter hints for all U functions
- quick compilation/syntax check

In the **Tools** directory you will find two files, **u.xml** and **u\_udl.xml**. The first one contains U functions, their parameters and short descriptions. The second one contains keywords and some other syntax information. You need to copy **u.xml** to **Notepad++/plugins/APIs**. Then start Notepad++ and select “View --> User-Defined Dialogue...”. Click the “Import” button and browse to the **u\_udl.xml**. This will load U syntax rules. You should now have the U entry in the Language menu.

If you want the code completion and function parameters hint features, you must enable them (Preferences → Backup/Auto-Completion). The recommended configuration is: “Enable auto-completion on each input”, “Function completion” and “Function parameters hint on input”. You can also change the “From nth character” setting to 2.

If you want a compilation as well, you need to install a plug-in. It is called NppExec. As you are done with the installation (just copy NppExec's files to the Notepad++ directory), you should be able to access the NppExec menu (in “Plugins”) and choose “Execute”. The command to enter in the dialog box is:

```
cmd /c chdir c:\fame && c:\fame\fame.exe "%$(FULL_CURRENT_PATH) "
```

Of course you might want to provide different path to Fame. You can save the command to be invoked later. Let's save it as “Execute Fame”. It's nice to have a key shortcut, so you can go to “Plugins --> NppExec --> Advanced Options”. In the “Menu items” section, you can add a new item, let's call it “Fame”. Then select a command you have just entered (Execute Fame). Now go to “Settings --> Shortcut Mapper” and select the “Plugin commands” tab. Find “Fame” and assign your favorite compilation key shortcut to it. Restart Notepad++. Please note that the key might have been already mapped to some other command – better check it twice!

Last but not least, if an error is found in a script, you probably wish to know the exact place where the error occurred. This can be done in “Plugins --> NppExec --> Console Output Filters”. Place a check mark next to a free slot and type in:

```
%LINE%: error*
```

You can also change font color (on the right) to 0xFF, 0x00, 0x00 (red) and make it bold, so that error messages differ from regular output. Now, as the game engine encounters an error during a syntax check, it will appear in the Notepad++ console in red. You can even double-click the error message and you are immediately transferred to the line that contains the error. Now you have a complete IDE for developing Fame scripts! :-)

## U Scripting Language

Plenty of things in the game (including conversations with NPCs) are set up using a scripting language called U. It is not necessary to be good at any programming language to make mods. You can only use a small subset of its features to create simple quests. Using U can extend your possibilities greatly, though.

At the moment, U is interpreted, not compiled. This means that it's terribly slow, but you don't have to worry about the compilation stuff. Actually, compilation IS supported, but executing compiled code is not. Nevertheless, you can make an EXE file out of your script (and it's not a script injected into interpreter's executable – it's really compiled!). This feature is as pretty as it's useless ;-).

You can write your scripts in any text editor and use the game engine to execute them, as well as to just test its correctness. Please refer to the manual for details on the engine's command line.

Several character encoding types can be used, but UTF-8 without BOM is recommended, as it is widely accepted as a portable encoding type.

## ***Script types***

There are four major script types in Fame. They all share the same \*.u extension and have the same syntax, but they are executed in slightly different manners. The types are:

- NPC scripts
- Global declarations
- General purpose scripts
- Trade profiles
- Location scripts
- Item scripts
- The Handler
- The OnLoad Script

The first (and "the most popular") group contains dialog scripts. They handle chatting with NPC's and all the stuff it involves (quests!). They also may contain some adjustments of NPC's parameters (the ones that cannot be set in monsters.ini), e. g. trade profiles. These are the only files that allow defining actions. What is more, statements outside actions are not allowed here. The only exception are variable declarations, which can be placed anywhere in a NPC script. For details, see the 'Writing dialog scripts' chapter.

The 'Global declarations' group contains declarations of global variables only. Currently, there is only one file in this group; it is the `_global.u` file. The variables declared in that file are available in ALL other script files. The file name is preceded by the underscore character to make it appear on top of the list when you display it in your file manager. This is very important file.

The 'General purpose scripts' group are 'usual' scripts. They have no constraints about the contents; they may contain almost everything (except actions). Currently, there are no files in this group. As the game develops, there will be probably much more files of the general purpose group.

The fifth group are trade profiles. They make it possible for the hero to trade with NPCs. See 'Writing Trade Profiles' for more details about this group.

The next group are location scripts. They consist of two predefined callback functions, `OnEnter` and `OnExit`. The `OnEnter` function is called every time the hero enters the locations, and the `OnExit` function is called when they leave the location. You can use the functions from the `DiffXXX` group to obtain last visit time and perform some action based on the time difference (for example: delete some of the location monsters if 7 days have passed).

Item scripts are invoked when items are used. The exact action depends on item category. Currently, only one item category uses scripts (readable items; they invoke their scripts as they are read).

Handler is a special script that groups together various callback functions. It has been designed to be used primarily with tutorials (which usually display a pop up window in response to some user action, thus a callback is needed), but can be used for other purposes as well. The callbacks currently implemented are:

- `OnNewGameStart` – called when a new game starts
- `OnChatEnd (MonType)` – called when the hero ends a talk with somebody, `MonType`

specifies NPC type index

- `OnEnterLoc (LocWorldX, LocWorldY)` – called the hero enters a location, `LocWorldX` and `LocWorldY` specify the world coordinates of the location
- `OnKill (MonsterID, PosX, PosY)` – called when the hero kills a monster or NPC, `MonsterID` specifies monster or NPC ID (that can be obtained by a call to `AddMonster`)
- `OnPickUpItem (ItemType, Param)` – called when the hero picks up or equips an item, `ItemType` specifies item type; `Param` is inventory ID of the slot where the item has been placed, when it's less than 17, the item is currently being equipped

The last group is the `OnLoad` script. There can be only one `OnLoad` script in the game and it appears as the `_onload.u` file. Its role is to initialize the game; it should load the world file, select a default location, set hero's attributes, etc.

The `OnLoad` script contains one important callback function, `OnChooseWeaponSkill`.

```
function OnChooseWeaponSkill (SkillID)
```

The function is called when the player confirms creation of a new character and it is time to equip him with weapons appropriate for the chosen weapon skill.

## ***Language basics***

### **General information**

The U language is NOT case sensitive. You can type its statements in lowercase, UPPERCASE, camelCase, even in TeEnIeBlOgGiEcAsE, just as you wish to.

### **Simple commands**

There are few commands you can use primarily for debug purposes, for example to print text in the console window (if it is present, of course). They act much like usual procedures, but they do not require parentheses for their argument list. You can separate arguments from the command name by almost any character (usually it is space, though) and you can separate one argument from another by any non-digit and non-letter character (but usually it is comma character). Just look at the following examples.

#### ***The Print and Println commands***

The Print command, as you probably expect, prints text on the screen (i. e. in the console window).

syntax:

```
Print <text>  
Println <text>
```

These commands only work when console window is present and it exists mainly for debugging purposes.

#### ***The Input command***

The Input command allows you to read keyboard input:

Syntax:

```
Input <variable>
```

User must hit Enter key to end typing. All entered white-space characters are skipped (i. e. if you enter several words separated by spaces, only the first word will be actually read into the variable). This command only works when console window is present and it exists mainly for debugging purposes.

## ***The System command***

The System command allows script to execute system commands. What exactly you can do with System command, it depends on the operating system you are using.

Syntax:

```
System <command>
```

Example:

```
system "dir"
```

This example will execute the `dir` command (listing files in the current directory). This command exists mainly for debugging purposes.

## ***The Incr and Decr commands***

The `incr` keyword is an abbreviation for 'increment'. It just adds 1 to the specified variable, e. g.:

```
var my_var = 5  
incr my_var
```

...makes `my_var` evaluate to 6. The `decr` command, as you guess, does the opposite.

## ***The Exit command***

The `exit` command ends execution of the script immediately.

## Comments

All the characters following the `'/'` sequence (up to the line-break) are treated as comments (just like in C++). You can enter anything you want there and it will not affect your program.

There are no block comments in U (unlike C++, where we do have the slash-asterisk and asterisk-slash sequences). You can only use multiple `'/'`.

Example:

```
print "This line will execute."  
print "This one too."  
//print "But this one will not. It's commented out."  
print "And this one will be executed normally..."
```

## Variables

The variables can be declared with the `var` keyword. There are no variable types in U. You can only store integer numbers in variables. More specifically, an unsigned 64-bit value is reserved for each variable. However it is not recommended to use values larger than `INT_MAX-1`.

A variable declaration looks like this:

```
var MyVariable 0
```

or equivalently (and maybe more familiar to programmers):

```
var MyVariable = 0
```

Please note that both leading and trailing space is required when using the '=' character here (unlike C/C++, where the spaces are optional and much unlike Bash programming, where they make a syntax error!).

The character '0' at the end of the declaration is a value which we assign to the variable immediately after its creation (i. e. we initialize the variable with the value).

Naming of variables must conform to some rules:

- first character must be an alphabetic character (A-Z)
- the rest of characters must be alphabetic characters or underscore characters ('\_')

So, the following names are valid:

```
var MyVariable1 0
var My_variable 0
```

...while the following are not:

```
var 1MyVariable 0 // error!
var _MyVariable 0 // error!
```

Please note that variable names are NOT case sensitive (unlike the C++, and much unlike the Linux!).

Depending on scope, we can distinguish three types of variables:

- global variables
- local variables (module scope)
- local variables (block scope)

The first kind of variable is easiest to distinguish, because every global variable is declared in the `_global.u` file, which we have already discussed of.

Local variables can be declared either outside or inside a block of code. We will know more details about it as soon as we talk about functions. At the moment we can only say that all local variables (both "module" ones and "block" ones) are only "visible" in a file they are declared in.

You can assign a value to a variable at any time:

```
var a 0
println "Variable declared."
a = 5
println "Variable value changed."
```

You can use the `print` and `println` commands to write variable's value to the output:

```
var a = 1
println a
```

## Conditionals

### *The basics of conditional expressions in U*

As in almost every programming language, in U you can check conditions too. And as in almost every programming language, you have the 'if' statement. It works much like its "cousin" from C/C++, meaning that it can accept complex conditions like:

```
if (MyVar == 33 && (MySecondOne != MyThirdOne || MyFourthOne))
{
    println "Condition is true."
}
```

As in the C/C++, variables are implicitly "converted" to Boolean type in logical expressions. More precisely (as there's actually no Boolean type in the U), all non-zero values are evaluated as 'true' and zeros are evaluated as 'false'.

The difference between the C/C++ and the U is that you **MUST** follow the 'if' statement by '{' and '}' characters, even if there is only one command in the block:

```
if (cnd)
{
    println "Something"
}
```

There are no C-like shortcuts like:

```
if (cnd)
    println "Something" // syntax error in U!
```

### *The 'else' block*

The `else` block can be used together with the `if` statement:

```
if (cnd)
{
    println "Something"
}
else
{
    println "Something else"
}
```

We have talked about the rules you must follow when creating an `if` block. The same rules apply for the `else` block.

The `else` and `if` statements can be used together to form a more complex language constructs

like:

```
if (cnd)
{
  println "Something"
}
else if (cnd2)
{
  println "Something else"
}
else
{
  println "Something different"
}
```

## Operators

The operators you can use to construct conditions are very similar to the ones known from C/C++. They have the same symbols (with one small exception), the same priority and other features. The available operators are:

Operator name	Symbol	Quick example
Equal	==	var1 == var2
Not equal	!=	var1 != var2
Not	!	!var1
And	&&	var1 && var2
Or		var1    var2
Xor (eXclusive or)	^^	var1 ^^ var2

As you probably know, in C/C++ there's no operator like '^'. But in U there are no bit-wise operators (like '&' or '|' in C/C++), so the xor operator has been assigned the '^' symbol, just to make it look more like the other logical operators ('&&', '||'). In C/C++ you have the '^' operator, which does exactly the same.

## Loops

Loops are constructs that simplify repetitive tasks greatly in common programming languages, although in U they are rarely used. Nevertheless, they do exist. The syntax is Basic-like, example:

```
for i = 0 to 10
{
  println ("something")
}
```

There is no way to change step value, so loop counter is always incremented by one.

Additional control over loops is provided by keywords: `break` and `continue`. The `break` statement exits the loop immediately, while the `continue` keyword skips all the statements following it and begins a new iteration. Similar behavior can be observed in languages like C, C++ or Java.

If the variable used by a loop is a global variable or module local variable, the variable name is hidden (like in C++). Block local variables cannot be hidden, so it's an error to use them as a loop counter. You can also use a non-existent variable name as a counter, it will be created automatically in this case.

## Functions

Function is a set of commands with assigned name and sometimes with a parameter list, returning some value as it ends its execution.

In U, functions have some differences when compared to popular programming languages like C++ or Pascal. Here they are:

- every function must return a value, but it can return implicitly
- when using an implicit return, a value of 0 is returned
- you must return a constant value or nothing (which equals returning 0), you cannot return a variable
- only an unsigned integer values can be returned
- only an unsigned integer values can be used as parameters (although some built-in functions can also have string and float parameter types)
- there are no default values for parameters
- parameter values are always passed by value, there are no references nor pointers
- you can only use a returned value to:
  - assign it to a variable
  - use it in a conditional expression
- you cannot overload functions
- there are no inline functions
- there is only one, default calling convention

Functions in U are similar to C++ in that:

- functions with no parameters are allowed (although you still must include parentheses)
- you can use parameters as if they were local variables (you can change their value too)
- you are not obliged to use function's return value (just like in C++)
- you can recursively call functions (i. e. you can call a `MyFunc` function from inside of `MyFunc`)

Unlike C++ or Pascal, you need not to declare functions. Once you have a definition (i. e. function's body), you also have the function declared. You do not even have to place the definition on the top of the file. It can be almost anywhere in the file and it will be "visible" to any call.

Syntax:

```
function <name> (<parameter_list>)  
{  
    <commands>  
    [<return_statement>]  
}
```

You do not specify function's type nor parameters' type, because you only use one type (unsigned integer). Instead you use the "function" keyword to declare a function. You must include parentheses even if you do not have any parameters.

You can place any number of return statements. The compiler will warn you if you do not have one, but it will not warn when not all control paths would return a value! It just checks whether any return command exists in the function's body.



Example:

```
function seven()  
{  
  return 7  
}
```

The following example shows how to use parameters:

```
function test (four, nine)  
{  
  if (four == 4 && nine == 9)  
  {  
    println "Everything is fine."  
    return 1  
  }  
  else  
  {  
    println "Something is wrong..."  
    return 0  
  }  
}
```

You can use the returned value in the following ways:

```
test (4, 9) // do not use the returned value at all  
  
if (test(4, 9)) // use it in a conditional expression  
{  
  println "Function succeeded."  
}  
  
var a = test (4, 9)
```

The following example shows an implicit return. If `arg` is equal to 10, we return a value of 1 explicitly, but if `arg` is something else, we do not have the `return` statement at all, which means that the function returns automatically and the return value is 0:

```
function Fun (arg)  
{  
  if (arg == 10)  
  {  
    println "Arg is ten."  
    return 1  
  }  
  else  
  {  
    println "Arg is not ten."  
  }  
}
```

We can also use “naked” return statement, i. e. without a value:

```
function Fun (arg)
{
  if (arg == 10)
  {
    println "Arg is ten."
    return
  }

  return 1
}
```

For a list of predefined functions, see the "Predefined functions" chapter.

## Labels

Yes, the infamous 'goto' command is available too. Although in modern programming languages like C++ it is generally not recommended to use 'goto', in game scripting languages like U it can prove to be very useful, as the U doesn't have many other control statements (like 'break' or 'continue' in C++).

You declare and use labels as follows:

```
if (Cnd1)
{
    if (Cnd2)
    }
    goto MyLabel
}
println "This line will be skipped if Cnd2 is nonzero."
}
```

```
MyLabel:
    println "Here we are!"
```

You may use 'goto' almost anywhere in code, but there are some restrictions connected with actions, which we are going to discuss later.

## **Inheritance**

*The inheritance mechanism implementation may be incomplete and thus it is not recommended to use it.*

U language allows you to inherit things from other scripts you or somebody else has already written. There is one important limitation: it can only create flat inheritance hierarchy (script B can inherit from A and C can inherit from B at the same moment but C won't automatically inherit from A then).

You indicate that script is derived from another script by adding the `extends` keyword.

Syntax:

```
extends <script_file_name>
```

This syntax may lead to some confusion, suggesting that the whole script file is inherited. This is only partially true, as only functions and variables are actually inherited. Any other elements (procedures, actions and so on, also any elements outside function blocks) are ignored.

We will refer to the script given by the `script_file_name` parameter as to "base script". We will also refer to the script having the `extends` keyword as "derived script".

The script file name must not include a path. Base script must reside in the same directory as the derived script.

## Inheriting functions

When a function is called from the derived script, the U interpreter searches the derived scripts and if it finds a function of the given name, it gets called. If such function is not found, then the base script is searched and matching function is called (if found).

If you have a function `MyFunction` in your derived script and it also exists in the base script, you should precede the `MyFunction` definition in the derived script by the keyword `overridden`. You can call the base `MyFunction` from the overridden one, using the keyword `super`.

Note: `super` may not work correctly in the current version of the engine. Use with care or better avoid.

Example:

*[scriptbase.u]*

```
function MyFunction (arg1, arg2)
{
  println "Base script here!"
}
```

*[derived.u]*

```
extends "scriptbase.u"
```

```
overridden function MyFunction (arg1, arg2)
{
  println "Derived script here!"
  super // let the base script do its job too
}
```

In the above example both texts will be written in the console window, because we have used the keyword `super`, making a call to the base function.

Please note that the derived version of function must have the same number of parameters as the base version. The parameter names may differ.

## Inheriting variables

You can refer to variables declared in the base script from the derived script. However, if you declare a variable named `MyVar` in the derived script and you had declared a variable of the same name `MyVar` in the base script, only the one from the base script will be used whenever you refer to the `MyVar` name. Therefore you should always keep in mind the list of variables from the base script and avoid using the names from the list when declaring new variables in the derived script.

## ***Writing dialog scripts***

Dialog designing is based on actions. Every NPC has its own (and only one) dialog script (that is, an \*.u file) containing a set of actions. An action is an atomic unit of dialog. One action can be used in one or more different dialogs with a certain NPC. Also, a set of actions (and/or their order) used in a certain dialog can change during play time, if the script writer wishes to.

## Actions

Actions are constructions similar to procedures. They are sets of commands with an assigned name. There are several major differences, though:

- you cannot nest actions like you do with procedures
- there's no way to call actions directly from outside an other action; they can only be called from the 'option' command (only if user selects the option enumerated by that command); it can only be placed in an action block one (and only one!) action is always preceded by the 'default' keyword; it marks a default action (the one that starts up the dialog)
- you can (but don't have to) initialize the 'text' property of the current action; its value is displayed on screen and can be seen by the player as the NPC's talk. You can set this property more than once per single action; only the last assign counts. If you do not set 'text' at all, the action's commands shall be normally executed, but in that case you should make sure that you leave the action properly (by 'end', 'trade', or 'shift' command), as the dialog options shall not be displayed on screen, even if they have been enumerated
- you can (but don't have to) place one or more 'option' commands in the current action to give the player a number of choices. If you don't enumerate any dialog option, the dialog shall end immediately (but action text, if present, shall be displayed).
- you cannot use 'goto' command from inside an action
- you cannot place labels in an action (i. e. you cannot jump into them by 'goto')
- you cannot place procedure definitions ('def\_proc') in an action, but you still can call procedures defined outside

You usually treat an action as a single 'NT-YR' (NPC Talks, You Reply). A single action defines text displayed on screen (this is the NT), and several possibilities of player's replies (these are the YRs).

Another (quite rare) possibility to use an action is a scheme referred to as 'MR' (Multi-Reply). As you can observe, buttons that display player's replies have only limited space for text, so these replies must be as short as possible. That's not fair! NPC can even talk us to death, and we can only say a word or two... Let's stop that! So there's a small trick available and it has already been mentioned; you do not set 'text' property for the action and - voila! - text from the previous action does not disappear from screen, but you are able to speak again!

## Control flow in actions

All statements inside an action are executed as they were inside procedures; so does the option statement (it adds a new dialog option to a local list; the list is destroyed as we leave the action block). An assignment of 'text' property works in a similar way. After execution of all action's statements, we enter the modal loop. Then, the dialog window is handled as every window does - the control is delegated to the main game engine. By the moment the player chooses some dialog option, control is returned to the script; we jump into the action selected by player and the scheme continues.

Here's an example of a short conversation:

```
default action hello
{
  text = "Hi, stranger."
  option "Hello.", hello2
  option "Goodbye", end
}

action hello2
{
  text = "I'm actually not supposed to talk to you, so you should
go now."
}
```

This one starts with action 'hello' (because it is default). The NPC says “Hi, stranger” and the hero has two possible replies: “Hello.”, which leads to action named 'hello2', and “Goodbye”, which ends the conversation. If the player selects the button “Hello.”, the action 'hello2' is executed and another text is displayed. Action 'hello2' has no more dialog options, so only one button can be selected now – clicking it just ends conversation.

You may change a default action any time, using the `SetDefaultAction` command:

```
SetDefaultAction hello2
```

Since then, 'hello2' is the default action and conversation with this NPC begins from 'hello2'.

## Items

An important thing is that the scripting engine gives you an access to the Player's inventory. You can add items to the inventory or take them from the Player, you can also check if the Player has specified item in the inventory.

To handle items, you use *item definitions*. An item definition is:

```
<item alias> <item name> <quantity> <durability_requirements>  
<status_requirements>
```

*Item alias* is a name you give to an item to identify it in the current script file. An alias declared in one file is not recognized anywhere else (unless you declare the same alias elsewhere). It also does not lead to any conflict if you declare two aliases with the same name in two different files. Aliases are fully local beings.

*Item name* is the name of the item provided in the items.ini file.

*Quantity* - as you can see, quantity is assigned to every item.

*Durability\_requirements* and *status\_requirements* - not fully implemented yet, although you are required to specify these parameters too (setting them to 0, usually).

An example of item definition:

```
item "The debt", "gold piece", 200, 0, 0
```

What do we have here? It's just 200 gold pieces, identified in the script file by the string alias "The debt". You can now use the definition to check if the Player has at least 200 gold pieces to pay some debt:

```
if (HeroHasItem ("The debt"))  
{  
    DoSomething()  
}
```

...or to check if the Player has ANY gold:

```
if (HeroHasSomeItem ("The debt"))  
{  
    DoSomething()  
}
```

You must put item definitions on the top of the file, before all actions that could potentially use them. Otherwise you will probably get an error message "undefined item" or something like that.

Common thing to do with item definitions is to take items from player and to give items to him. For example, we could inform the Player that he has paid his debt, so we can return his jacket to him:

```
if (HeroHasItem ("The debt"))  
{
```

```
TakeItem ("The debt")
GiveItem ("Hero's jacket")
}
```

Of course, the "Hero's jacket" string is also an item definition alias.

You can also specify corpses as items, but this is slightly different. As you may have noticed, corpses are not usual items in the sense that they are not defined in the items.XX.ini file. Therefore, writing:

```
item "Goblin's remains", "goblin corpse", 1, 0, 0 // wrong!
```

...will not work. Instead, you can write:

```
item "##Goblin's remains", "goblin", 1, 0, 0
```

Thus, you specify monster's name instead of item's name, and item alias follows two hashes (#). Whenever game engine sees item alias beginning with hashes, it assumes that item's name is actually monster's name and it should 'create' a corpse out of it.

Instead of item name, one may specify its number, following a single hash character (#). This is a zero-based index of the item definition as it appears in the items.XX.ini file. For instance, the following declaration specifies a short sword, because it's the first entry in the items file:

```
item "a non-magical sword", "#0", 1, 0, 0
```

This is very useful when referencing items that do not have a unique name.

## Repairs

Some NPCs would repair your damaged items. To display the repair window (i. e. inventory window in repair mode), you just redirect current action to 'repair', just as you would do with trade window:

```
option "Can you repair my weapons?", repair
```

Repair cost for 1 damage point is the value of item divided by its maximum durability, rounded to the nearest integer and doubled. For example, a broad sword is normally worth 250 gold pieces, so when its durability equals 39/40, then total repair cost is 12 gold pieces. Every NPC has exactly the same way of calculating repair cost (unlike trade prices).

## Curing

Some NPCs have medical skills and are able to cure hero's diseases and/or restore their missing limbs. This is done in the similar fashion as item repairs – as a special dialog option redirection:

```
option "Can you cure my diseases?", cure
```

```
option "Can you restore my limbs?", cure_limbs
```

Note that cure not only removes all diseases, it also restores Hit Points, as well as it removes bleeding/poisoned status and fixes broken limbs.

Also note that cure\_limbs only applies to limbs that have been non-permanently chopped off. It doesn't fix broken limbs nor it restores permanently lost limbs.

## Butchery and Cooking

Some NPCs have butchery or cooking skills which can be triggered in similar way to repairing or curing:

```
option "Will you take care of this flesh?", butchery
```

```
option "Can you cook this meat?", cooking
```

In case of Butchery, the first appropriate corpse from the hero's inventory is used. The hero also needs some money (5 gold pieces) as a payment. This is done automatically, so you don't have to implement the payment in the script.

In case of Cooking, the first appropriate piece of raw meat from the hero's inventory is used. The hero also needs some money (5 gold pieces per piece of meat) as a payment. This is done automatically as well.

## Traveling through locations

Some NPCs would join hero and visit various locations along with him. As they reach a specific destination, the `OnEnterLoc` function is called in the NPC script (if it is present, of course). You might want to use it to provoke some activity, for example the NPC can comment the new place. It looks like this:

```
function OnEnterLoc (LocWorldX, LocWorldY)
{
    if (LocWorldX == 15 && LocWorldY == 23)
    {
        NPCUnfollowHero()
        SetDefaultAction "hello2"
        incr Quest17Counter
        NPCSetActivity ("Aruos", "#1", 17) // wander
        NPCStartChat ("Aruos", "#1")
    }

    return 0
}
```

The callback function has two parameters, `LocWorldX` and `LocWorldY`, which identifies the location. Usually you want to test the parameters against some criteria. It is quite reasonable for NPC to stop following the hero if they reached their final destination, set new activity type and/or to start a chat.

## Dialog script localization

All script examples in this reference assume that there is only one language defined in the game. However, the mod creator has a possibility of create quests that work fine with several different languages. In case of dialog scripts, this is done by writing dialogs in all supported languages at once. Languages can be separated by '|' character:

```
default action hello
{
  text = "Witaj, przyjacielu. Co mogę dla ciebie zrobić?|Welcome,
my friend. What can I do for ya?"

  option "Ktoś ty?|Who are you?", who
  option "Helo|. Spytać o coś można?|Hello. Can I ask you a
question?", question
  option "Pohandlujemy?|Let's trade!", trade
  option "Potrafisz naprawiać przedmioty?|Can you repair items?",
repair
  option "Spadaj?|Get lost!", end
}
```

In this simple example, we have two languages supported: Polish (first one) and English (second one). This order is determined by an entry in the `\Data\game.ini` file, which looks like this:

```
all_available_langs = "pl|en"
```

If you have specified two languages in `game.ini`, then you **MUST** supply all dialog texts in two languages. If you forget to do this, the script won't compile. If you don't wish your mod to support more languages, you must change the above `game.ini` entry.

## OnGiveItem

This is a callback function used to handle giving items to NPCs. The syntax is:

```
function OnGiveItem (Type, FlagIdentified, FlagUnique,
FlagBlessed)
```

The parameters allow the script to decide whether the NPC accepts the item or not and generally what to do with the item.

Type – item type

FlagIdentified – equal to 1 if the item has been identified, 0 otherwise

FlagUnique – equal to 1 if the item is unique (artifact), 0 otherwise

FlagBlessed – equal to 2 if the item is blessed, 4 if cursed, 0 otherwise

The return value is important – it tells the engine the “decision” of the NPC. Possible values are:

Value	Meaning
-------	---------

1	Accepted – item has been accepted by the NPC. If this flag is not set, the item is not taken from the player's inventory.
2	Remove – item will be removed from the player's inventory
4	Talk – the NPC will start a dialog with the player
8	Identify – the NPC will attempt to identify the item. This requires special variables - <code>_Identify</code> and <code>_ItemType</code> .

The values in the above table can be combined, e. g. the value of 13 (8+4+1) means that the item is accepted, the NPC will try to tell something to the player and will also identify the item.

Whenever 8 is returned (most likely combined with other flags), the script is expected to have declared two special variables: `_Identify` and `_ItemType`. Both should be initialized to 0. When `OnGiveItem` returns, `_ItemType` is set to the type of the given item, so that further script calls are able to access and use it (the value of the `Type` parameter in `OnGiveItem` cannot be assigned to other variable in the script because of the scripting language limitations). `_Identify`, on the other hand, is meant to be written by the script rather than read. The script is expected to set the variable to 1 as soon as the NPC decides that the item will be actually identified (for example, he made sure that the player character has enough money to pay for the service).

## Dropping items

NPCs will drop items when killed. The recommended way to have NPCs dropping non-important items is to use the `init` function in a dialog script and the `NpcAddInvItem` function to set up NPC's inventory:

```
function init()
{
    NpcAddInvItem ("", "#1", "gold piece")
}
```

Please note, however, that NPC's inventory is available during the game, so that the items from it may be stolen, destroyed or lost in any other way. Even if this is not currently implemented, it may be in the future, so you should only consider the inventory as potential, non-guaranteed drop. If you need the NPC to drop a guaranteed item, use the `OnDeath` function instead:

```
function OnDeath(x, y)
{
    AddItemEx ("", "gold piece", 10, x, y)
}
```

## Writing trade profiles

Some NPCs can trade with the hero. If you want NPC to trade, you must do three things:

- create (in dialog script for the NPC) an action leading to 'trade'
- create a trade profile for the NPC
- create a connection between the dialog script and the trade profile

The first thing is easy:

```
action Example
{
  text = "Do you want to trade with me?"
  option "Yeah, sure.", trade
  option "Not now.", end
}
```

You do not define the 'trade' action. Even more: you can't do it, because 'trade' is a reserved word. It doesn't actually name an action. It closes the dialog window and opens the trade window. If the trade is completed, you do not return to the dialog window any more until you [T]alk to the NPC again - please consider this when constructing a dialog!

The second important thing to do is the trade profile itself. It must be placed in a separate \*.u file, but you can reuse one trade profile for many different NPCs. It enables you to create several common profiles, e. g. a standard village shopkeeper profile, a city chemist profile, a merchants' guild member profile, a lone traveling merchant profile, etc.

A typical trade profile consists of two sections. First one enumerates all the items that NPC has for sale or exchange. Second one enumerates whole categories of items. For example, if the NPC is a blacksmith, it will probably offer weapons, armor, occasionally materials and tools.

The items section is used to determine which items the NPC has for sale. The categories section is used to determine whether the NPC would buy an item from the hero or not.

The syntax is following:

```
DefineTradeItem (<item_name>, <supply_freq>, <min>, <max>)
```

*item\_name* – Name of the item (from items.XX.ini)

*supply\_freq* – Number of days that the merchant receives supply of new items of that type

*min* – Minimum amount of items of that type offered by merchant

*max* – Maximum amount of items of that type offered by merchant

Example:

```
DefineTradeItem ("short sword", 7, 1, 3)
```

The above definition causes the trader to offer 1 to 3 short swords. If all the sword are sold out, the trader receives brand new ones in a week.

Feel free to experiment with various constructions, like:

```
if (QuestCompleted)
{
    // offer ordinary weapons only
}
else
{
    // offer powerful artifacts too
}
```

The second section of a trade profile enumerates categories of items that the trader is willing to buy from the Player. It is done by another simple function, `DefineBuyCategory`. It takes just one parameter. The parameter is a category number. You can find a complete list of available category numbers in the chapter “**Ini Files**”.

Example:

```
DefineBuyCategory (12)
DefineBuyCategory (13)
```

These definitions cause the trader to buy only rings (category 12) and amulets (category 13) from the Player.

To assign a trade profile to the NPC, do something like this (in NPC's dialog script!):

```
LoadTradeProfile ("vlg-blacksmith.u" 2.0, 0.5, 1, 100, 5000)
```

All functions used above are explained further in this document.

## Writing location scripts

As already explained, the location scripts typically contain only two functions, `OnEnter` and `OnExit`. They do not have any standard purpose. You can leave them empty if you want, but you should not attempt to create a location script without one of these functions inside. The location script must be placed in the `/Data/Scripts/Locations` directory (note that this is NOT the same directory as `/Data/Locations!`) and must have a proper file name. The file name is determined by location file name. For example if the location file is `village.map`, then the location script should be named `village.u`. You are not obliged to create the script for every location you have.

Here is an example of `OnEnter` function. It sets up a battle between townspeople of Manhattan and some goblins when the hero visits the location for the first time:

```
function OnEnter()
{
  incr VisitCounter
  if (VisitCounter == 1)
  {
    AddGroup ("goblins")
    AddGroup ("townspeople")

    AddMonsterToGroup ("goblin", "manhattan", 4, 8, "goblins")
    AddMonsterToGroup ("goblin", "manhattan", 6, 10, "goblins")
    AddMonsterToGroup ("goblin", "manhattan", 10, 8, "goblins")
    AddMonsterToGroup ("goblin", "manhattan", 8, 5, "goblins")
    AddMonsterToGroup ("goblin", "manhattan", 4, 4, "goblins")

    NPCSetGroup ("Aldag", "#1", "townspeople")
    NPCSetGroup ("Guard", "#1", "townspeople")
    NPCSetGroup ("Orirk", "#1", "townspeople")
    NPCSetGroup ("Ukurug", "#1", "townspeople")

    Battle ("goblins", "townspeople", "goblins vs. townspeople")
    MsgLog ("STR_USER_BATTLE1", 2)
  }

  return 0
}
```

The visit counter is increased every time the `OnEnter` is called (i. e. when the hero enters the location). Please note that it must be a global variable declared in `_global.u`. If the counter equals 1 (first visit), the two groups are created, one for monsters and the other for townspeople. NPCs (townspeople) need to be placed in the editor before you call `NPCSetGroup`. The `AddMonsterToGroup` just adds a new monster. Then both parties are assigned to their groups.

After the initialization the battle begins and a message is displayed in the game log. Please note that you use string identifiers here rather than the actual strings. You can add your custom messages to **Data/strings.XX.txt**.

Another example uses a time difference function to determine when the player has visited the location for the last time and prints an appropriate message in the console window:

```
function OnEnter()
{
    if (DiffSeconds() > 60)
    {
        println "It's been a long time since you visited this location."
    }
    else
    {
        println "You returned very quickly..."
    }

    return 0
}
```

You can also use a function named `OnInit`. It is called automatically by the game engine when the location is created (once per location). This is a very good place to create and assign groups, even a better one than `OnEnter` (because you don't need a visit counter).

An important feature of location scripts is the ability to set up alarms. Alarms can be raised when certain conditions are met – player performs a particular action and the game responds with a predefined reaction. Currently, only one type of alarm is supported: when a member of a previously defined group is attacked, the other members will try to kill the attacker. It can look like that:

```
function OnInit()
{
    AddGroup ("townspeople_akeram2")

    NPCSetGroup ("Leran", "#1", "townspeople_akeram2")
    NPCSetGroup ("Upores", "#1", "townspeople_akeram2")
    NPCSetGroup ("Ezerela", "#1", "townspeople_akeram2")
}

alarm SelfDefence
{
    GroupMemberAttacked "townspeople_akeram2", attack
}
```

## ***Writing item scripts***

The item script is invoked when the player performs some action on an item. For instance, when the player reads a book, the `OnRead` function is called in the script (currently it is the only function supported in the item script). The script file must be present in the `Data/Scripts/Items` directory. If it does not exist, no further action is performed by the game engine. Example script contents:

```

function OnRead (Type)
{
    if (Type == 181)
    {
        ReportRead = 1
        MsgBox ("STR_STORY_REPORT")
    }
    else if (Type == 226)
    {
        TextBox ("STR_DIARY")
    }
    else
    {
        return 1
    }

    return 0
}

```

A typical action is to present a message to the player. `MsgBox` is suitable for short messages, while `TextBox` contains scroll bars and thus is able to display a longer piece of texts.

It is expected that you return 0 if the item of the given type is readable. Any other return value (e.g. 1) results in a default message box saying that there was nothing interesting to read (or something similar).

## **Starting item sets**

At character creation, player is able to choose among several item sets that the character will have in their inventory at the beginning of the game. The sets can be defined in the scripts. Two scripts are involved here: the `OnLoad` script and the global declarations script (`_global.u`).

The first step (in the global declarations file) is to define the item sets. They look just like good old item definitions that can be found in most of dialog scripts. The only difference is that you cannot freely choose their names. They must have the form of “SetX\_ItemY”, where X is a number of set (from 1 up to the number of sets defined) and Y is an index of item in the set (from 1 up to 3).

```

item "Set1_Item1", "short sword", 1, 0, 0
item "Set1_Item2", "gold piece", 100, 0, 0
item "Set1_Item3", "potion of healing", 3, 0, 0
item "Set2_Item1", "long knife", 1, 0, 0
item "Set2_Item2", "arrow", 100, 0, 0
item "Set2_Item3", "potion of healing", 3, 0, 0

```

Having the sets defined, you now need to handle them in the `OnLoad` script. You can declare a function named `OnChooseItemSet` that is called just after the character has been created by the player. Its only argument contains an index of the current item set:

```

function OnChooseItemSet (ChosenItemSet)
{
    if (ChosenItemSet == 1)

```

```

{
    AddInvItemByAlias ("Set1_Item1")
    AddInvItemByAlias ("Set1_Item2")
    AddInvItemByAlias ("Set1_Item3")
}
else if (ChosenItemSet == 2)
{
    AddInvItemByAlias ("Set2_Item1")
    AddInvItemByAlias ("Set2_Item2")
    AddInvItemByAlias ("Set2_Item3")
}
}

```

In this example the player chooses from two item sets.

Starting equipment is another story. It depends mainly on the chosen weapon skill. For example if the player chooses swords, he will get one, but if they choose staves, they will be equipped with a wand or staff (and some “magical” clothes, most likely). There's another callback function in the OnLoad script for that purpose:

```

function OnChooseWeaponSkill (SkillID)
{
    if (SkillID == 1) // swords
    {
        // equip a sword
    }
    else if (SkillID == 2)
    // ...etc., etc...
}

```

## **Functions**

### **ActivateSpecial function**

Activates a special object at specified position.

**Script types:**

*all*

**Syntax:**

`ActivateSpecial (loc_uid, x, y)`

**Description:**

Activates special object at  $(x, y)$  in location *loc\_uid*. See also `DeactivateSpecial`.

### **AddCompanion function**

Adds a monster or NPC to accompany the hero.

**Script types:**

*all*

**Syntax:**

`AddCompanion (npc_or_monster_name, npc_identity)`

**Description:**

The parameter *npc\_or\_monster\_name* is a name from [monster.ini](#). The second parameter can be omitted for monsters. For NPCs that do not have more than one identity (which is true for most cases), specify “#1” as *npc\_identity*.

### **AddDragon function**

Adds a dragon to the specified location.

**Script types:**

*all*

**Syntax:**

`AddDragon (loc_uid, dragon_name, x, y)`

**Description:**

The *loc\_uid* parameter is an UID of a location in which the dragon is going to be added. Position is given by *x* and *y* parameters.

Note that this is currently the only way to add dragon to the game, as you cannot add dragons in the Location Editor (unlike other monsters).

## **AddGroup function**

Adds a new group to the game.

### **Script types:**

*all*

### **Syntax:**

```
AddGroup (group_name)
```

## **AddInvItem function**

Adds an item to hero's inventory.

### **Script types:**

*all*

### **Syntax:**

```
AddInvItem (item_name, count)
```

### **Description:**

Adds items to hero's backpack. The items are never put in the current equipment (even if there's no room in the backpack and there are some equipment slots free), so you can specify count.

If there are no free slots in the backpack, an exception is thrown (error message appears and the game exits).

## **AddItem function**

Adds an item into specified location (the item is dropped on the ground).

### **Script types:**

*all*

### **Syntax:**

```
AddItem (loc_uid, item_name, x, y)
```

### **Description:**

The new item count equals 1. The `loc_uid` parameter can be an empty string; in that case the item is added in the current location.

## **AddItemEx function**

Adds an item into specified location (the item is dropped on the ground). This variant allows to specify the count.

### **Script types:**

*all*

### **Syntax:**

```
AddItemEx (loc_uid, item_name, count, x, y)
```

### **Description:**

The `loc_uid` parameter can be an empty string; in that case the item is added in the current location.

## **AddInvItemByAlias function**

Adds an item defined by the `item` command to hero's inventory.

### **Script types:**

*all*

### **Syntax:**

```
AddInvItemByAlias (item_alias)
```

### **Description:**

This function requires an item definition given by the `item` command. It makes it possible to add a set of items chosen during the character creation, but can also have other uses.

If there are no free slots in the backpack, an exception is thrown (error message appears and the game exits).

### **Example:**

```
item "my sword", "short sword", 1, 0, 0
```

```
AddItemByAlias ("my sword")
```

## AddInvItemEx function

Adds an item to hero's inventory.

### Script types:

*all*

### Syntax:

AddInvItemEx (item\_name, count, flags, data, material)

### Description:

This functions behaves much like AddInvItem, but allows extra parameters:

flags – item flags, explained below

data – additional data, explained below

material – from what the item has been made (iron, mithril etc.). Available materials are listed in **Data/mat.XX.ini**

Item type	Purpose of data
Spell books & scrolls	designates spell index from <b>Data/spells.XX.ini</b>
Mould	created item type
Other	not used

Item flags are:

Value	Flag name	Description
1	flgBSIdentified	The blessed/cursed state has been revealed to player.
2	flgBlessed	The item is blessed (better than normal).
4	flgCursed	The item is cursed (worse than normal).
8	flgIdentified	The item is identified (all its special powers and attributes have been revealed to player, except blessed cursed state).
16	flgBSRandom	The blessed/cursed state of the item is determined randomly.
32	flgPoisoned	The item is poisoned.
64	flgActivated	The item has its primary function activated (e. g. a torch is lit)
128	flgVirtual	The item does not exist (do not use explicitly!)

Some of these flags can be combined. You cannot use flgBSRandom along with flgBlessed or flgCursed. An item cannot be blessed or cursed at time (i. e. you cannot combine flgBlessed and flgCursed). All other combinations are allowed.

### Example:

```
AddInvItemEx ("short sword", 1, 0, 0)
```

## AddLocLightEffect function

Sets up a special lighting effect in the specified location.

### Script types:

*all*

### Syntax:

```
AddLocLightEffect (alpha, r, g, b)
```

### Description:

The color is made using four components (alpha, R, G, B). The alpha component specifies level of opacity and should not be too low. All of the components should be in range 0-255.

## AddLocSoundEffect function

Sets up a special sound effect in the specified location. It is emitted with a specified (random) interval as a log message.

### Script types:

*all*

### Syntax:

```
AddLocSoundEffect (loc_uid, time, interval, chance, time_flags,  
str_tag)
```

### Description:

The effect is added to location *loc\_uid*. Time must be equal to *time* (given in seconds) and divisible by *interval*. *Chance* determines probability of the event (the higher the value, the less probable the event). String with the tag *str\_tag* is used.

*time\_flags*:

1 - day only

2 - night only

3 - night and day

## AddMonster function

Adds a new monster.

### Script types:

*all*

**Syntax:**

AddMonster (loc\_uid, mon\_name, x, y)

**Description:**

Adds a new monster to location *loc\_uid* and places it at (*x*, *y*). The added monster will never leave the specified location (does not follow the hero when they go through a staircase or other portal type).

Returns ID of the added monster or -1 if the location did not exist. The returned ID can be considered as unique (i. e. you can later use it for comparisons, for example to check whether the monster has been killed).

**AddMonsterToGroup function**

Adds a new monster and assigns it to a group.

**Script types:**

*all*

**Syntax:**

AddMonsterToGroup (loc\_uid, mon\_name, x, y, grp\_name)

**Description:**

Adds a new monster to location *loc\_uid*, places it at (*x*, *y*) and assigns it to the group *grp\_name*.

**AddObject function**

Adds a terrain object into the specified location.

**Script types:**

*all*

**Syntax:**

AddObject (loc\_uid, obj\_type, x, y)

**Description:**

Adds the object of type *obj\_type* to location *loc\_uid* and places it at (*x*, *y*).

*obj\_type* – object type (number) from **objects.XX.ini**.

**AnyAliveMonsters function**

Checks whether there are any hostile monsters left in the specified location. Dead monsters do not

count.

**Script types:**

*all*

**Syntax:**

`AnyAliveMonsters (loc_uid)`

**Description:**

`loc_uid` is the UID of the visited location you want to examine. The function returns nonzero (true) if the location has never been visited by hero, even if the location contains no alive monsters.

## Battle function

Starts a battle between two groups of monsters/NPCs.

**Script types:**

*all*

**Syntax:**

`Battle (group_1_name, group_2_name, battle_name)`

**Description:**

The `battle_name` parameter is used since then to identify the battle event and you may refer to this name whenever you need to refer to some battle (e. g. to retrieve battle results).

## BeginQuest function

Adds a new quest log entry.

**Script types:**

*all*

**Syntax:**

`BeginQuest (quest_id, npc_name, loc_uid, desc_tag)`

**Description:**

The `quest_id` can be anything you want, as long as it is unique. Be careful when calling the matching `EndQuest` – it should use exactly the same `quest_id`.

The `npc_name` parameter should be the name of the NPC that charged hero with the quest.

The `loc_uid` parameter should be the UID of the location where the NPC is or where they can be met when the quest is about to be completed.

The `desc_tag` parameter must appear in the string resource file and identifies a string containing the quest's brief description.

**See also:**

`EndQuest`

## Chance function

Returns a non-zero number with a specified probability.

### Script types:

*all*

### Syntax:

Chance (min, max)

### Description:

There is a probability of min/max that the function will return 1. Otherwise it returns 0. The function will also return 0 in each one of the following cases:

- if min is greater than max
- if min is negative
- if max is negative.

## CreateDungeonSite function

### Script types:

*The OnLoad Script*

### Syntax:

CreateDungeonSite (size\_x, size\_y, num\_levels, loc\_file\_name, enter\_x, enter\_y)

### Description:

Creates a site of random dungeons. The site consists of several levels (the number is given by *num\_levels*). Each level is *size\_x* cells wide and *size\_y* cells high. The entrance to the dungeon is placed in the location given by name *loc\_file\_name* (must contain .map extension), at coordinates *enter\_x*, *enter\_y*.

The dungeons are randomly generated every time the hero enters them. It means that only one dungeon level at time is actually remembered. If the hero leaves one random dungeon level and travels to another one, the previous one is lost forever, along with its items left behind, monsters etc.

The dungeon site (as you already know, actually it is just one location) is placed at first "free" position in the current world. "Free" means that at the position *size\_x* \* *size\_y* cells have undefined default terrain type and are not assigned a location loaded from file. If the current world has not enough "free" cells or all the "free" cells are spread through the world, the world is resized to fit our new dungeon location with specified size.

You must call CreateDungeonSite AFTER you have called SetStartLoc. Otherwise the game will crash. You should call the CreateDungeonSite function only in the OnLoad script.

## DeactivateSpecial function

Deactivates a special object at specified position.

### Script types:

*all*

### Syntax:

```
DeactivateSpecial (loc_uid, x, y)
```

### Description:

Deactivates special object at  $(x, y)$  in location *loc\_uid*. See also `ActivateSpecial`.

## DefineBuyCategory function

Adds a category of items to trade.

### Script types:

*Trade profiles*

### Syntax:

```
DefineTradeItem (category_id)
```

### Description:

The *category\_id* must be a valid category ID. For a complete list of available categories, please see 'INI Files' chapter.

## DefineRandomTradeItem

Defines a random trade item in NPC's trade window.

### Script types:

*Trade profiles*

### Syntax:

```
DefineRandomTradeItem (supply_freq, max_value)
```

### Parameters:

*supply\_freq* – Number of days that the merchant receives supply of new items of that type

*max\_value* – Maximum value of the item (gold pieces)

## DefineTradeItem function

Defines an entry in NPC's trade window.

### Script types:

*Trade profiles*

### Syntax:

```
DefineTradeItem (item_name, supply_freq, min, max)
```

### Parameters:

*item\_name* – Name of the item (from items.XX.ini)

*supply\_freq* – Number of days that the merchant receives supply of new items of that type

*min* – Minimum amount of items of that type offered by merchant

*max* – Maximum amount of items of that type offered by merchant

## DelayedMsgBox function

Makes a message box pop up after the current dialog is finished.

### Script types:

*NPC scripts*

### Syntax:

```
DelayedMsgBox (msg_tag)
```

### Description:

If you use the `MsgBox` function in the NPC script, it will appear on top of the dialog window, which is not quite what is usually desired. Thus the `DelayedMsgBox` has been introduced. It does not pop up until the dialog window has been closed.

The `msg_tag` parameter denotes string identifier (the string must be present in the `strings.XX.ini` file).

Also see `DelayedMsgBox` for a message box that appears after the NPC dialog has been finished.

**See also:** `MsgBox`, `TextBox`

## DeleteAllItems function

Deletes all items at the specified position in the specified location.

### Script types:

*all*

### Syntax:

```
DeleteAllItems (loc_uid, x, y)
```

### Description:

All items lying on the ground at  $(x, y)$  are removed.

## DeleteAllMonsters function

Deletes all monsters in the specified location.

### Script types:

*all*

### Syntax:

```
DeleteAllMonsters (loc_uid)
```

### Description:

Monsters are deleted, not killed (no corpses remain!).

## DeleteItem function

Deletes a single item at the specified position in the specified location.

### Script types:

*all*

### Syntax:

```
DeleteItem (loc_uid, item_name, x, y)
```

### Description:

Only an item with a matching name and lying on the ground at  $(x, y)$  is removed.

## DeleteObject function

Deletes a terrain object at the specified position in the specified location.

### Script types:

*all*

### Syntax:

```
DeleteObject (loc_uid, x, y)
```

### Description:

Only the object at  $(x, y)$  is removed, terrain tile remains the same.

## DiffDays function

Returns the difference (in days) between the current time and last visit time for the current location.

### Script types:

*all*

**Syntax:**

`DiffDays ()`

**Description:**

Returns 0 on error (when last visit time is earlier than the current time). The maximum value that can be returned is 86400 (about 240 years). If the actual difference is more than maximum, the maximum value is returned.

**DiffHours function**

Returns the difference (in hours) between the current time and last visit time for the current location.

**Script types:**

*all*

**Syntax:**

`DiffHours ()`

**Description:**

Returns 0 on error (when last visit time is earlier than the current time). The maximum value that can be returned is 1036800 (about 240 years). If the actual difference is more than maximum, the maximum value is returned.

**DiffMonths function**

Returns the difference (in months) between the current time and last visit time for the current location.

**Script types:**

*all*

**Syntax:**

`DiffMonths ()`

**Description:**

Returns 0 on error (when last visit time is earlier than the current time). The maximum value that can be returned is 2880 (about 240 years). If the actual difference is more than maximum, the maximum value is returned.

**DiffSeconds function**

Returns the difference (in seconds) between the current time and last visit time for the current location.

**Script types:**

*all*

**Syntax:**

DiffSeconds ()

**Description:**

Returns 0 on error (when last visit time is earlier than the current time). The maximum value that can be returned is 3732480000 (about 240 years). If the actual difference is more than maximum, the maximum value is returned.

## DiffYears function

Returns the difference (in years) between the current time and last visit time for the current location.

**Script types:**

*all*

**Syntax:**

DiffYears ()

**Description:**

Returns 0 on error (when last visit time is earlier than the current time). The maximum value that can be returned is 240. If the actual difference is more than maximum, the maximum value is returned.

## EndQuest function

Marks the specified quest log entry as 'completed'.

**Script types:**

*all*

**Syntax:**

EndQuest (quest\_id)

**Description:**

The `quest_id` must identify a quest log entry previously added by an appropriate `BeginQuest` call.

**See also:**

`BeginQuest`

## EquipAmmo function

Equips hero with specified type of ammo.

**Script types:**

*all*

**Syntax:**

EquipAmmo (item\_name, item\_count)

**Description:**

This function works much like `EquipItem`, but it includes an additional parameter, `item_count`.

**EquipAmmoBS function**

Equips hero with specified type of ammo, allowing to specify blessed/cursed state for the ammo.

**Script types:**

*all*

**Syntax:**

```
EquipAmmoBS (item_name, item_count, flags)
```

**Description:**

For possible `flags` values, see `AddInvItemEx`.

**EquipItem function**

Equips hero with specified item

**Script types:**

*all*

**Syntax:**

```
EquipItem (item_name)
```

**Description:**

This function creates a new item and places it in the hero's current equipment. For example:

```
EquipItem ("short sword")
```

...Makes the hero start with a short sword in his hand. If we add another call with a "helm" parameter, our hero receives a helm additionally. Of course it is placed on his head, not in his hands. As you can see, the proper part of equipment is matched automatically. If nothing matches the specified item, an exception is thrown (error message appears and the game exits).

If the item cannot be equipped for some reason (for example, the item is a short sword and the hero has currently his right arm chopped off), the item will be added to the inventory. In turn, if the item cannot be placed in the inventory, it will be dropped on the ground under hero's feet.

The function should not be used to add ammo (like arrows, belts etc.), because it doesn't allow to specify item count. In this case use `EquipAmmo` instead.

## EquipItemBS function

Equips hero with specified type of item, allowing to specify blessed/cursed state for the item.

### Script types:

*all*

### Syntax:

```
EquipItemBS (item_name, flags)
```

### Description:

For possible flags values, see AddInvItemEx.

## GiveItem function

Adds specified item to hero's inventory.

### Script types:

*all*

### Syntax:

```
GiveItem (item_alias)
```

### Description:

The item with the specified alias must be declared first. If hero cannot carry the specified item for whatever reason (e. g. the item is too heavy or there is no more room in the inventory), the item is dropped on the ground.

## HasGroupWonBattle function

Returns nonzero if the specified group has won the specified battle. If the battle hasn't been finished yet, zero is returned.

### Script types:

*all*

### Syntax:

```
HasGroupWonBattle (group_name, battle_name)
```

### Description:

This function is location-unsafe (if you use it, you must ensure that the location of the battle is the current location).

## HasHeroItem function

Checks whether hero has specified item.

**Script types:**

*all*

**Syntax:**

HasHeroItem (item\_alias)

**Description:**

Checks whether hero has specified item. Quantity does matter (i. e. must be equal or greater than the quantity specified in definition of item\_alias).

**HasHeroSomeItem function**

Checks whether hero has specified item.

**Script types:**

*all*

**Syntax:**

HasHeroSomeItem (item\_alias)

**Description:**

Checks whether hero has specified item. Quantity does NOT matter (i. e. hero must have at least one item, even if specified item alias defines more than one item).

**HeroGetAppearance function**

Retrieves hero's appearance attribute.

**Script types:**

*all*

**Syntax:**

HeroGetAppearance ()

**Description:**

none

**HeroGetDexterity function**

Retrieves hero's dexterity attribute.

**Script types:**

*all*

**Syntax:**

HeroGetDexterity ()

**Description:**

none

## **HeroGetIntelligence function**

Retrieves hero's intelligence attribute.

### **Script types:**

*all*

### **Syntax:**

```
HeroGetIntelligence()
```

### **Description:**

none

## **HeroGetSkillLevel function**

Retrieves hero's skill level.

### **Script types:**

*all*

### **Syntax:**

```
HeroGetSkillLevel (skill_name, level_count)
```

### **Description:**

For more details about `skill_name` see `HeroLearnSkill`.

## **HeroGetStrength function**

Retrieves hero's strength attribute.

### **Script types:**

*all*

### **Syntax:**

```
HeroGetStrength()
```

### **Description:**

none

## **HerolsAnyLimbMissing function**

Returns 1 if any of hero's limbs (an arm or leg) is missing.

### **Script types:**

*all*

**Syntax:**

HeroIsAnyLimbMissing()

**Description:**

Ignores permanently lost limbs (returns 0 in that case). Broken limbs do not count as missing (0 returned as well).

This function is intended to be used together with the `cure_limb` special redirection.

**HeroGetVitality function**

Retrieves hero's vitality attribute.

**Script types:**

*all*

**Syntax:**

HeroGetVitality()

**Description:**

none

**IdentifyItemType function**

Identifies all items of the specified type.

**Script types:**

*all*

**Syntax:**

IdentifyItemType (item\_name)

**Description:**

This function makes sense only when used with items that needs identifying for the whole type, like magical scrolls, spellbooks or plants. It reveals the true name (and purpose, most of the times) of an item type, but not blessed/cursed state of the concrete item.

**HeroLearnSkill function**

Makes hero learn a new skill or advance its level.

**Script types:**

*all*

**Syntax:**

HeroLearnSkill (skill\_name, level\_count)

**Description:**

`skill_name` is a name stored in **Data/strings.XX.txt** under identifier like `STR_OTHER_SKILL_xxx`.

If hero did not have specified skill before, they learn it at level `level_count` (usually this parameter is equal to 1). Otherwise, they advance the skill level by `level_count`. The minimum skill level is 1 and maximum is 100. If skill level is already 100, the function has no effect. If `level_count` plus current skill level exceeds 100, the skill level is advanced to 100.

**IsBattleEnded function**

Returns nonzero if the specified battle has been ended (all monsters from one of the fighting groups had perished).

**Script types:**

*all*

**Syntax:**

```
IsBattleEnded (battle_name)
```

**Description:**

This function is location-unsafe (if you use it, you must ensure that the location of the battle is the current location).

**IsPlayerWoman function**

Checks hero's gender.

**Script types:**

*all*

**Syntax:**

```
IsPlayerWoman ()
```

**Description:**

Returns 0 for male or nonzero for female. The gender is determined by the player at the game start-up.

## LoadTradeProfile function

Loads specified trade profile, assigns it to current NPC and sets up common NPC's trading parameters.

### Script types:

*NPC scripts*

### Syntax:

```
LoadTradeProfile (sell_mult, buy_mult, trade_skill, min_cash, max_cash)
```

`sell_mult` - Sell multiplier (e. g. 2.0)

`buy_mult` - Buy multiplier (e. g. 0.5)

`trade_skill` - Trade skill (e. g. 1)

`min_cash` - Minimum of cash (e. g. 100)

`max_cash` - Maximum of cash (e. g. 5000)

If you buy an item, its value is multiplied by parameter 1., giving the price (an amount of money you pay to the merchant). It should be greater than or equal to 1, but in some rare circumstances it can be less than 1.

If you sell an item, its value is multiplied by parameter 2., giving the price (an amount of money you receive for the item). It should be less than 1, giving the merchant an opportunity to earn some money for his work.

The parameter 3. determines how hard it would be to negotiate prices with the merchant. A trade skill of 1 is the lowest possible value and means that the NPC doesn't know a thing about how to trade. He would probably accept any crap for any sum of money you propose. But it is very unusual to encounter a merchant like this; you will much more often deal with experienced traders (trade skill up to 100), who will rather take the last shirt from you than allow anybody to cheat them for a single piece of gold.

The parameters 4 and 5 determine how much money will NPC own every time you visit him. Note that the values are not absolute; if you sell the NPC a very precious artifact, he may have much more than the limit until some time has passed and he has had an opportunity to spend the money :-). And if he pays you all the money he has got, he will have 0 gold pieces (even if the minimum is higher) until you revisit him after some time.

## MsgBox function

Displays a message in a modal window.

### Script types:

*all*

### Syntax:

```
MsgBox (msg_tag)
```

### Description:

The `msg_tag` parameter denotes string identifier (the string must be present in the strings.XX.ini

file).

If you decide to use this function in the OnLoad script, place it in the `AfterStart` function. For more info please see `AfterStart`. Also see `DelayedMsgBox` for a message box that appears after the NPC dialog has been finished.

**See also:** `DelayedMsgBox`, `TextBox`

## MsgLog function

Displays a new message in the message log.

### Script types:

*all*

### Syntax:

`MsgLog (msg_text, msg_importance)`

### Description:

The `msg_importance` parameter can be one of the following values:

- 0 – default (let the fate decide ;-))
- 1 – information (white text, green square)
- 2 – important message (yellow text, red square)
- 3 – critical message (red text, red square)

If you decide to use this function in the OnLoad script, place it in the `AfterStart` function. For more info please see `AfterStart`,  
For an example, see the **Writing location scripts** chapter.

## NpcActivate function

Activates specified NPC.

### Script types:

*all*

### Syntax:

`NpcActivate (loc_uid, npc_name, npc_identity)`

### Description:

`NpcActivate` activates specified NPC identity. Each NPC can have multiple identities (entries in `Data\monsters.XX.ini`). They may differ slightly (for example, have different pictures), but share the same name. Identity name is specified in the `monsters.XX.ini` file as *description* parameter and usually equals '#1'. If you want to add more identities of the same NPC, you usually would name them '#2', '#3' and so on. For more details, please refer the description of `monsters.XX.ini` file.

`NpcDeactivate` does just the opposite.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

## **NpcAddEnemy function**

Adds specified NPC to the other NPC's enemy list.

### **Script types:**

*all*

### **Syntax:**

```
NpcAddEnemy (loc_uid, npc_name, npc_identity, enemy_name,  
enemy_identity)
```

### **Description:**

For more info about identities, see `ActivateNPC`.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

## **NpcAddInvItem function**

Adds an item to NPC's inventory.

### **Script types:**

*all*

### **Syntax:**

```
NpcAddInvItem (npc_name, npc_identity, item_name, item_count)
```

### **Description:**

The player can retrieve the item after killing the NPC. The `item_name` parameter refers to the name in the `items.XX.ini` file.

Note that neither `npc_name` nor `npc_identity` can be empty (as opposed to most of other NPC functions).

For more info about identities, see `ActivateNPC`.

## **NpcAddSpell function**

Enables this NPC to cast the spell.

### **Script types:**

*all*

### **Syntax:**

```
NpcAddSpell (npc_name, npc_identity, spell_name, spell_level)
```

### **Description:**

Enables this NPC to cast the spell at specified level. Name of the spell, given as `spell_name` parameter, comes from the **spells.XX.ini** file. Spell level must be 1-100 and designates spell strength (its meaning is different for each spell, but generally: the higher level, the better spell). Note that neither `npc_name` nor `npc_identity` can be empty (as opposed to most of other NPC functions).

For more info about identities, see `ActivateNPC`.

## **NpcDeactivate function**

Deactivates specified NPC.

### **Script types:**

*all*

### **Syntax:**

```
NpcDeactivate (loc_uid, npc_name, npc_identity)
```

### **Description:**

See `NpcActivate` for more details.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

## **NpcFollowHero function**

Makes the current NPC follow the hero.

### **Script types:**

*all*

### **Syntax:**

```
NpcFollowHero (loc_uid, npc_name, npc_identity)
```

### **Description:**

See also `NpcUnfollowHero`.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

## **NpclsAlive function**

Checks whether specified NPC is alive or not.

**Script types:**

*all*

**Syntax:**

```
NpcIsAlive (loc_uid, npc_name, npc_identity)
```

**Description:**

Returns nonzero value if specified NPC is alive or 0 if he (she) has been killed. The `npc_name` specifies NPC's name (like 'Griswold'), while `npc_identity` is usually "#1", which is default identity for all NPCs.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

For more details about NPC identities, see `NpcActivate` function.

## NpcIsPresentInLoc

Checks whether specified NPC is present in the location.

**Script types:**

*all*

**Syntax:**

```
NPCIsPresentInLoc (loc_uid, npc_name, npc_identity)
```

**Description:**

Returns nonzero value if specified NPC is present in the location `loc_uid`. The location must be loaded. The `npc_name` specifies NPC's name (like 'Griswold'), while `npc_identity` is usually "#1", which is default identity for all NPCs.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

For more details about NPC identities, see `NpcActivate` function.

## NpcKill function

Kills specified NPC.

**Script types:**

*all*

**Syntax:**

```
NpcKill (loc_uid, npc_name, identity)
```

**Description:**

The function just finds a location using given location UID, then finds a NPC with matching name and identity, then makes the NPC dead.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

## **NpcMakeHeroEnemy function**

Makes the hero an enemy of the specified NPC.

### **Script types:**

*all*

### **Syntax:**

`NpcMakeHeroEnemy (loc_uid, npc_name, npc_identity)`

### **Description:**

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

## **NpcSetActivity**

Sets NPC's current activity.

### **Script types:**

*all*

### **Syntax:**

`NpcSetActivity (loc_uid, npc_name, npc_identity, activity)`

### **Description:**

The `activity` parameter actually stands for AI profile name. For a list of available values, please refer to the chapter “Monster definitions”.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

## **NpcSetAttitude function**

Changes NPC's attitude towards the hero.

**Script types:**

*all*

**Syntax:**

```
NpcSetAttitude (loc_uid, npc_name, npc_identity, attitude)
```

**Description:**

This is commonly used in dialog scripts to make NPC attack if he/she gets angry while talking with the player or to calm down. Possible `attitude` values are: 0 – neutral, 1 – friendly, 2 – hostile.

If `npc_name` is not specified (empty string), the current hero's interlocutor is assumed, but this behavior works properly only when the function is used in dialog scripts.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

## **NpcSetGroup function**

Finds a NPC named `npc_name` (he or she must already exist somewhere, it is not added automatically with this call) and assigns him/her to the group `grp_name`.

**Script types:**

*all*

**Syntax:**

```
NpcSetGroup (loc_uid, npc_name, npc_identity, grp_name)
```

**Description:**

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

For more info about identities, see `NpcActivate`.

## **NpcStartChat function**

Opens a dialog window and begins a chat with the specified NPC.

**Script types:**

*all*

**Syntax:**

```
NpcStartChat (loc_uid, npc_name, npc_identity)
```

**Description:**

Please note that opening a dialog window means invoking a modal loop, so this should be the last command in the script.

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty

string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

For more info about identities, see `NpcActivate`.

## **NpcUnfollowHero function**

Makes the current NPC stop following the hero.

### **Script types:**

*all*

### **Syntax:**

```
NpcUnfollowHero (loc_uid, npc_name, npc_identity)
```

### **Description:**

The `loc_uid` parameter specifies the location where the NPC is to be found. It can be an empty string, which means current location.

Both `npc_name` and `npc_identity` can be empty strings, which denotes current NPC (i. e. the one that is chatting with the player).

See also `NpcFollowHero`.

## **Reveal function**

Reveals the current location

### **Script types:**

*all*

### **Syntax:**

```
Reveal (param)
```

### **Description:**

`Reveal` just causes hero to see all cells in the current location. If we don't call `Reveal` after setting up a starting location, hero will see only the cells being currently in his FOV (Field Of View).

The `param` value can be safely ignored. It is reserved for future use. You can just put 0 here.

The function needs a location, so calling `Reveal` before a call to the `SetStartLoc` function will result in a nice crash.

## **Rnd function**

Returns a random integer number.

**Script types:**

*all*

**Syntax:**

Rnd (min, max)

**Description:**

If min is greater than max, the function returns max.

## SetStartLoc function

Sets starting location.

**Script types:**

*The OnLoad Script*

**Syntax:**

SetStartLoc (loc\_file\_name, hero\_x, hero\_y)

**Description:**

Makes the game start in the location loaded from the *loc\_file\_name* file. The file should have the '.map' extension, which you must also include in the *loc\_file\_name*. If *loc\_file\_name* does not contain '.map', the game engine assumes that it is location UID. You should call SetStartLoc immediately AFTER the LoadWorld function. If you do not keep this order of calling, the behavior of the game will be undefined. You must not call the SetStartLoc function more than once. You should call the SetStartLoc function only in the OnLoad script.

It also sets up hero's starting position. Our hero will be initially placed at the (*hero\_x*, *hero\_y*) cell of the specified location.

## Sleep function

Makes the game sleep for a specified amount of time.

**Script types:**

*all*

**Syntax:**

Sleep (milliseconds)

**Description:**

All input is disabled while the application is sleeping. The screen is redrawn before the sleeping is committed, so that all changes invoked from the script before the call for the Sleep function are reflected.

## Takeltem function

Removes specified item form hero's inventory (if it is there).

**Script types:**

*all*

**Syntax:**

```
TakeItem (item_alias)
```

**Description:**

The item with the specified alias must be declared first. If hero does not have the item (or the item count is not sufficient), nothing happens.

**TextBox function**

Displays (potentially long) text in a window.

**Script types:**

*all*

**Syntax:**

```
TextBox (msg_tag)
```

**Description:**

The `msg_tag` parameter denotes string identifier (the string must be present in the strings.XX.ini file).

See also: `DelayedMsgBox`, `MsgBox`

**TutorialShow function**

Displays specified tutorial page.

**Script types:**

*all*

**Syntax:**

```
TutorialShow (stage_tag)
```

**Description:**

Although this function can be used in all script types, it is the best to place it in the Handler. See the appropriate section for more information,

**TutorialStage function**

Checks if the specified tutorial stage is the current stage.

**Script types:**

*all*

**Syntax:**

TutorialIsStage (stage\_tag)

**Description:**

Although this function can be used in all script types, it is the best to place it in the Handler. See the appropriate section for more information,

## Keyword list

The following is an alphabetical list of all reserved words in U. You must not use them as identifiers (variable names, action names or function names). Depending on the context, some of these keywords may be actually allowed as identifiers, but don't rely on this behavior, as in the near future this may be a subject of change.

You should also avoid using predefined function names as identifiers (the complete list can be found in this document).

```
action
alarm
call
companion_attack
companion_follow
companion_wait
cls
cure
cure_limb
decr
default
else
end
extends
for
function
goto
i+
i-
iadd
icmp
if
iin
iloop
incr
input
iout
ishl
ishr
isub
item
null
option
overridden
print
println
repair
return
super
system
```

text  
trade  
var

Additionally, you must not use this command name:

SetDefaultAction

# INI Files (Game Object Definitions)

## General information

Numerous game parameters are kept in INI files. They all reside in the **\Data** directory. Format of Fame INI files is very similar to Windows INI files, but internal (a lot faster) parser is used to deal with them, carrying several additional possibilities.

Several character encoding types can be used, but UTF-8 without BOM is recommended, as it is widely accepted as a portable encoding type.

## Sections

INI files are divided into sections. A file must have at least one section, and there must be at least one definition in each section (otherwise, it is ignored). No definition can be placed without a corresponding section.

## Section headers

Each section is designated by a header, which looks like:

```
[Name]
```

Header name must only contain alphanumeric characters. Spaces are not allowed. An underscore isn't allowed either.

## Numerical values

A definition should look like:

```
name = value
```

White spaces before and after the '=' sign are optional. You can also put more than one space between tokens, this is correct.

The hexadecimal notation is also allowed. It is especially useful for specifying colors. Hexadecimal values start from the '#' character. Color values usually consist of three hexadecimal octets (R, G, B). Example: #E8ECE8.

## Strings

Unlike Windows INI, you should double-quote all string values:

```
name = "value"
```

It is not actually a problem for simple parsers to handle strings without quotes, but it looks much more clearly, especially when there are many long definitions in a file.

## Data types

INI parser supports five data types: four integer ones (8-bit, 16-bit, signed/unsigned 32-bit) and string. These are: 'int' (-2147483648 to 2147483647), 'unsigned char' or 'uchar' (0 to 255), 'unsigned short' or 'ushort' (0 to 65535), 'unsigned int' or 'uint' (0 to 4294967295). Values with all bits set to 1 are considered invalid.

## Comments

All lines starting with semicolon ';' are treated as comments. If any spaces are followed by ';', they are ignored. You cannot place a comment in the same line as a definition.

```
INVALID DEFINITION:
```

```
value = 2342345 ; error
```

```
VALID DEFINITION:
```

```
; OK
```

```
value = 2342345
```

## Localization

INI file names conform to the following pattern: name.XX.ini, where XX is a language identifier (e. g. en – English). By default, all actual data are contained in Polish INI files, while English ones contain only text strings.

Current game language can be set through the **Data\game.ini** file. You can set *lang\_ini* and *lang\_script* parameters there as well (this changes language version of INI file that actual numerical parameters are read from).

## Monster definitions

Monster definition file has the following format:

```
[header]
monsters=N

[monster1]
parameter=value1

[monster2]
parameter=value2

...

[monsterN]
parameter=valueM
```

All parameters are optional, unless explicitly stated that they are required.

Parameter	Data Type	Description	Default
<i>ai</i>	string	AI profile name. See below.	“AI_ProfileHunter”
<i>brain</i>	string	Brain script file.	“monbase.u”
<i>color</i>	uint	Color (in the ASCII mode).	(gray)
<i>description</i>	string	Identity string for NPCs. In case of monsters it is ignored.	"New Monster"
<i>dexterity</i>	ushort	Monster dexterity. In the current version ignored.	0
<i>dmgl</i>	ushort	Minimum damage caused by monster.	0
<i>dmg2</i>	ushort	Maximum damage caused by monster.	0
<i>family</i>	ushort	Race (humanoids, undeads etc.). See below.	0
<i>features</i>	string	Special features possessed by the monster. See below.	(empty string)
<i>flags</i>	ubyte	Any combination of creature flags. See below.	0
<i>hp1</i>	ushort	Minimum Hit Points	0
<i>hp2</i>	ushort	Maximum Hit Points	0
<i>name</i>	string	Name (e. g. “goblin”). Required.	-
<i>nameb</i>	string	Name in accusative case. Required.	-
<i>named</i>	string	Name in genitive case. Required.	-
<i>namem</i>	string	Name in plural form. Required.	-

<b>Parameter</b>	<b>Data Type</b>	<b>Description</b>	<b>Default</b>
<i>namemd</i>	string	Name in plural form and genitive case. Required.	-
<i>occurrence</i>	ushort	Defines how frequently monster appears in random-generated locations.	5 = very often
<i>picindex</i>	ushort	Picture index in Data\monsters.bmp.	0
<i>resnormal</i>	ubyte	Melee resistance (0-100%).	0
<i>resmagic</i>	ubyte	Magic resistance (0-100%).	0
<i>resfire</i>	ubyte	Fire resistance (0-100%).	0
<i>rescold</i>	ubyte	Cold resistance (0-100%).	0
<i>resside</i>	ubyte	Resistance to side (sword-like) weapons (0-100%)	0
<i>resranged</i>	ubyte	Resistance to ranged weapons, including all thrown weapons (0-100%)	0
<i>resaxes</i>	ubyte	Resistance to axes (0-100%)	0
<i>resblunt</i>	ubyte	Resistance to blunt weapons, including hammers, mauls, maces, clubs (0-100%)	0
<i>ressilver</i>	ubyte	Resistance to weapons made from silver (0-100%)	0
<i>sound</i>	string	Description of a sound made typically by the monster. Used as a warning for the player.	(empty string)
<i>soundm</i>	string	Same as above, plural form.	(empty string)
<i>weight</i>	ushort	Monster weight.	0
<i>wpncateg</i>	ubyte	Weapon category. See below.	0

Melee resistance means resistance to all types of conventional weapon damage (non-magic). This value overrides *resside*, *resranged*, *resaxes* and *resblunt* if they are specified as well.

The *ressilver* parameter only applies when the attacker (typically the hero) is using a silver weapon and it overrides all other resistances.

## AI profiles

The *ai* parameter value can be:

<b>Value</b>	<b>Description</b>
AI_ProfileHunter	The monster actively seeks a prey (most likely the hero) and immediately attacks if only it can.
AI_ProfileLazy	The monster does nothing unless attacked.
AI_ProfileRanger	The monster is able to attack from distance. It will attempt to come

Value	Description
	closer to its enemy, but not too close. Otherwise it acts much like AI_ProfileHunter.
AI_ProfileWanderer	The monster wanders around randomly unless attacked.
AI_ProfileWizard	The monster is able to cast spells. Otherwise it acts much like AI_ProfileRanger.

## Families

The *family* parameter value can be:

Value	Description
0	Human
1	Humanoid (e. g. goblin)
2	Undead
3	Spider
4	Animal
5	Golem
6	Plant

Monster *family* determines many things. For example golems and undeads never retreat and do not bleed from their wounds and non-humanoids never makes fire when camping in the wilderness.

## Weapon categories

The *wpncateg* parameter can affect combat, e. g. monsters using teeth can bite off hero's leg while those who use fists cannot do that. Acceptable values are:

Category	Description
0	Bare fists or claws
1	Sword
2	Axe
3	Hammer
4	Bow or crossbow
5	Thrown weapon
6	Pole weapon
7	Knife
8	Staff
9	Teeth

## Flags

Monster flags are:

Flag name	Value	Description
<i>flgActive</i>	1	NPC is active, always 1 for monsters
<i>flgDragon</i>	2	Monster is a dragon (and is bigger than 1 tile).
<i>flgMale</i>	4	Monster is a male.
<i>flgFemale</i>	8	Monster is a female.
<i>flgSummonable</i>	16	Monster (or NPC) can be summoned by a spell.
<i>flgCommonNPC</i>	32	Only applies to NPCs. Common NPCs can have multiple instances at time (normal NPCs must be unique), but unlike monsters they can chat and trade with the hero. They can also have their own inventory and cast spells.
<i>flgCorpseInedible</i>	64	Only applies to NPC definitions. Most of corpses can be eaten by hero (some of them have special effects when eaten, but this is hardcoded in the C++), but some cannot (e. g. corpse of a golem).
<i>flgCanFly</i>	128	Monster can fly (cross the water tiles without drowning or slowing down)
<i>flgCanSwim</i>	256	Monster can swim (cross the water tiles without drowning)

## Features

Monster features can be:

Feature Tag	Feature Type	Description
attack-fire	No value	Monster can breath fire.
curse-equip	No value	Monster can curse hero's equipment.
damage-attacker	No value	Monster automatically damages the attacker.
deflect-spells	No value	Monster can deflect offensive spells.
drain-focus	Single value	Monster can drain hero's focus points.
thief	No value	Monster can steal hero's equipment.
teleport	No value	Monster can teleport.

“No value” means that the very presence of the feature tag is required. “Single value” means that a range of number is additionally required, “Double value” means that two ranges are required.

A “No value” feature can be specified as follows:

```
features = "thief"
```

A "Single value" feature can be specified as follows:

```
features = "drain-focus:3-5"
```

Despite the "single" word, a range must be specified. In the above example, the range is 3-5, meaning that 3 to 5 points of focus may be drain in a single turn.

Two or more different features can be specified as follows:

```
features = "drain-focus:3-5;curse-equip;deflect-spells"
```

## Item definitions

Item definition file has the following format:

```
[header]
items=N
```

```
[item1]
parameter=value1
```

```
[item2]
parameter=value2
```

...

```
[itemN]
parameter=valueM
```

All parameters are optional, unless directly stated that they are required.

Parameter	Data Type	Description	Default
<i>ac</i>	ubyte	Armor class. Applies only to armors, helms and shields.	0
<i>bonus</i>	string	List of additional special bonuses, see below.	""
<i>category</i>	ubyte	Category. Full list below.	18
<i>color</i>	uint	Color (in the ASCII mode).	(gray)
<i>data</i>	uint	Additional data. See remarks below.	0
<i>defmat</i>	ubyte	Default material (random material by default). See remarks below.	1
<i>dmgl</i>	ubyte	Minimal damage caused by item. Applies only to weapons.	0
<i>dmg2</i>	ubyte	Maximum damage.	0
<i>durab</i>	ushort	Durability (how much damage an item can receive before being completely destroyed).	0
<i>flags</i>	ubyte	Flags. See below.	0
<i>indefinite</i>	string	Indefinite article (valid for specific languages only, e. g. English)	"a"
<i>invpicindex</i>	ushort	Picture in inventory.	0
<i>name</i>	string	Item name. Required.	"New Item"
<i>nameb</i>	string	Item name in accusative form. Required.	"New Item"
<i>namem</i>	string	Item name in plural form. Required.	"New Item"
<i>namemd</i>	string	Item name in plural possessive form. Required.	"New Item"

<b>Parameter</b>	<b>Data Type</b>	<b>Description</b>	<b>Default</b>
<i>nutrition</i>	ushort	Nutrition. Applies only to food.	0
<i>occurrence</i>	ubyte	Determines if an item will appear in random-generated locations. 0 means that it will not, any non-zero value means that it will appear.	5 = very often
<i>picindex</i>	ushort	Picture in main game screen.	0
<i>value</i>	uint	Item value in shop. Equal to item's price when trader's attributes are: 1.0 and 1.0. This attribute also determines how frequently an item appears in random-generated locations.	0
<i>weight</i>	ushort	Item weight. Small items such as rings may weigh 0.	0

## Categories

Item categories are:

<b>Category number</b>	<b>Description</b>
1	Swords
2	Axes
3	Mauls, hammers & maces
4	Bows & crossbows
5	Thrown weapons
6	Pole weapons
7	Knives & daggers
8	Staves
9	Shields
10	Helms & caps
11	Armor
12	Rings
13	Amulets
14	Books
15	Scrolls
16	Potions
17	Valuables
18	Other
19	Food
20	Materials

Category number	Description
21	Tools
22	Explosives
23	Ammo

## Data

*Data* – the meaning of this parameter depends on item's category. It is explained in the table below:

Item category	Meaning of the 'Data' field
Spell books and scrolls	Spell index (please see the 'Spell definitions' chapter)
Moulds and rods	Type of item that can be created using the mould or rod
Unique items	Index of the unique item

## Material

Possible materials are defined in the mat.xx.ini file (where xx is language ID). Normally, 0 means “other material”, which is suitable for most of items. All other materials are metals, which are mostly used to create weapons and armor. 1 means “random material” (actually random metal). 2 is typically iron, 3 is copper etc.

## Flags

Item flags are:

Flag name	Value	Description
<i>flgUniqueItem</i>	1	Item is unique (artifact).
<i>flgSmallItem</i>	2	Item can be placed in sack.
<i>flgTwoHanded</i>	4	Item must be held in two hands (if weapon).
<i>flgReadable</i>	8	Item is readable.
<i>flgSpellbook</i>	8	Item is a spell book or scroll ( <i>Data</i> must be greater than 0, see above).
<i>flgAltCorpse</i>	16	n/a
<i>flgSacrifExcept</i>	16	Item can be sacrificed even if its <i>occurrence</i> parameter equals 0.
<i>flgBow</i>	32	Item can fire arrows.
<i>flgCrossbow</i>	64	Item can fire bolts.
<i>flgBottle</i>	128	Item is an empty bottle, vial or flask (not drinkable).

Flag name	Value	Description
<i>flgLightSource</i>	256	Item is a source of light (torch, lamp etc.)

To combine multiple flags, just add their values, for instance if you want your item to be an unique bow, set its flags to 33 or, more conveniently, to 1|32.

## Bonuses

Special item bonuses are defined using the Universal List Format (ULF). The syntax is:

`id1:n0_1-n1_1,m0_1-m1_1;id2:n0_2-n1_2,m0_2-m1_2`

The “id” parameter specifies a predefined identifier (see the table below). The value of a bonus is a random number from the range n0 to n1. The parameters m0 and m1 specify additional data (currently not used). The format allows an arbitrary number of bonuses, but currently only definitions with 2 bonuses are supported.

Available ids:

id	Description	Min	Max
<i>str</i>	Strength bonus	1	?
<i>dex</i>	Dexterity bonus	1	?
<i>vit</i>	Vitality bonus	1	?
<i>int</i>	Intelligence bonus	1	?
<i>app</i>	Appearance bonus	1	?
<i>nrm</i>	Melee (normal) damage resistance	1	100
<i>fir</i>	Fire resistance	1	100
<i>col</i>	Cold resistance	1	100
<i>mag</i>	Magic resistance	1	100
<i>poi</i>	Poison resistance	1	100

Examples:

ULF	Resulting bonus
<code>int:1-2,0-0</code>	+1 or +2 to Intelligence
<code>dex:2-2,0-0;str1-1,0-0</code>	+2 to Dexterity, +1 to Strength
<code>poi:5-5,0-0;vit1-2,0-0</code>	+5% Poison Resistance, +1 or +2 to Vitality
<code>fir:1-10,0-0</code>	+1-10% Fire Resistance



## Spell definitions

Spell definition file has the following format:

```
[header]
spells=N
```

```
[spell1]
parameter=value1
```

```
[spell2]
parameter=value2
```

...

```
[spellN]
parameter=valueM
```

All parameters are optional, unless directly stated that they are required.

Parameter	Data Type	Description	Default
<i>energyamount</i>	ushort	Energy amount used to cast spell (do not confuse with focus cost).	1
<i>focuscostbase</i>	ushort	Focus required to cast spell.	5
<i>flags</i>	ushort	Spell flags (explained below).	0
<i>icon</i>	ushort	Picture index used as quick spell icon.	0
<i>name</i>	string	Spell name. Required.	-
<i>needaim</i>	bool	If set to true (nonzero), spell needs aiming.	0
<i>neutrality</i>	ushort	Spell neutrality (0 – offensive, 1 – neutral, 2 – defensive)	1
<i>piccount</i>	ushort	Total number of spell animation frames.	1
<i>picstart</i>	ushort	Index of first image for spell effect animation.	0

You can change parameters of the existing spells if you want to, but please don't bother adding new spells – they will not work automatically.

## Flags

The spell flags are:

Flag	Value	Description
------	-------	-------------

<i>flgSummon</i>	1	The spell is a summon spell. It results in a creation of new monsters that will help the caster fighting their enemies.
<i>flgHeroOnly</i>	2	The spell can only be cast by hero. It is not suitable for NPCs.

## Terrain definitions

Terrain definition file has the following format:

```
[header]
terrains=N

[terrain0]
parameter=value1

[terrain1]
parameter=value2

...

[terrainN-1]
parameter=valueM
```

All parameters are optional, unless directly stated that they are required. Terrain definitions that have name of “???” (exactly three characters) are ignored.

Parameter	Data Type	Description	Default
<i>apmod</i>	ushort	AP modifier. Not used.	0
<i>automapcolor</i>	uint	32-bit color index on AutoMap in RGBA format. Hex value allowed (see: Numerical Values).	0 (black)
<i>char</i>	ubyte	Character (in the ASCII mode)	.
<i>color</i>	uint	Color (in the ASCII mode).	(gray)
<i>flags</i>	ubyte	Terrain flags. See below.	0
<i>name</i>	string	Terrain name. Required.	-
<i>nameb</i>	string	Terrain name in accusative form. Required.	-
<i>picindex</i>	ushort	Index of first picture (of 3 total).	0
<i>deflocname</i>	string	Default location name (it is used when name is not specified by the user). Required.	-

You can specify the special value #DEAD (or 57005) as *automapcolor*. Such an object is drawn on the auto-map using alpha value of 0 (i.e. it is fully transparent). This is useful for objects that shouldn't be displayed on the auto-map.

## Flags

Terrain flags are:

<b>Flag</b>	<b>Value</b>	<b>Description</b>
<i>flgSingleTile</i>	1	The terrain entry has only 1 bitmap tile assigned (usually has 3). Example: dungeon floor.
<i>flgInterior</i>	2	The terrain entry represents interior (weather effects does not affect it)
<i>flgWater</i>	8	The terrain entry represents water (hero can dive into it and swim).

## Object definitions

Please note that the word “Object” in this document sometimes refers to terrain objects (e. g. trees, walls, stones) and sometimes to game objects in general (including monsters, spells, items and so on). I know this is very confusing. I tried really hard to coin a better term, but failed miserably. You must live with it somehow.

Objects definition file has the following format:

```
[header]
objects=N
```

```
[terrain0]
parameter=value1
```

```
[terrain1]
parameter=value2
```

...

```
[terrainN-1]
parameter=valueM
```

All parameters are optional, unless directly stated that they are required.

Parameter	Data Type	Description	Default
<i>automapcolor</i>	uint	32-bit color index on AutoMap in RGBA format. Hex value allowed (see: Numerical Values).	0
<i>char</i>	ubyte	Character (in the ASCII mode)	#
<i>color</i>	uint	Color (in the ASCII mode).	(gray)
<i>flags</i>	ubyte	Object flags. Detailed list below.	0
<i>group</i>	ushort	Object group. Better not use :-).	0
<i>name</i>	string	Terrain name. Required.	-
<i>nameb</i>	string	Terrain name in accusative form. Required.	-
<i>picindex</i>	ushort	Index of first picture (of 3 total).	0

## Flags

Object flags are:

Flag name	Value	Description
<i>flgPassable</i>	1	Object is passable (hero can stand on it).

<b>Flag name</b>	<b>Value</b>	<b>Description</b>
<i>flgDestructible</i>	2	Not used.
<i>flgFlammable</i>	4	Not used.
<i>flgWater</i>	8	Object represents water (hero can dive into it and swim).
<i>flgObstructFov</i>	16	Object affects hero's Field of Vision (FOV)
<i>flgHurtsKicker</i>	32	Anyone who kicks this objects receives damage.
<i>flgDoor</i>	64	Object is a door (can be closed and opened)

These flags can be combined (see **Item Definitions**).

## Group

Defines object's group used by the Location Editor. There are too many objects that can be placed using the editor, so they cannot be shown all at once. Instead the object panel displays only several available objects on a single page and additionally uses groups for easier navigation.

<b>Group Number</b>	<b>Group Name</b>	<b>Special Group?</b>
0	Miscelanneous	no
1	Village	no
2	Wilderness	no
3	Desert	no
4	Dungeon	no
5	Burned Grounds	no
6	Town	no
7	Fortifications	no
8	(not used)	no
9	(not used)	no
10	(not used)	no
11	(not used)	no
12	Items	no
13	NPCs	no
14	Monsters	no
15	Terrains	no
16	Portals	no
17	Generators	no
18	Signs	no
19	Doors	no
20	Altars	no

21	Lodes	no
100	Big Objects	yes
200	Water Objects	yes
300	Walls	yes
400	Road Objects	yes

Special group numbers are used, as the name cleverly suggests, in a special way. They can be combined with other (“normal”) group numbers, so that they actually appear in both groups in the editor. For example, a section of a wall that typically appears in village buildings may have group number “301”, meaning that it belongs to the group “Village” (1) and the special group “Walls” (300).

## Hero definitions

Hero definitions specify gender and appearance of the hero. Player can choose between these definitions at the new game start-up. There are no string parameters in a hero definition, so they are language independent. They are stored in `hero.ini`. The file has the following format:

```
[header]
heroes=N

[hero0]
parameter=value1

[hero1]
parameter=value2

...

[heroN-1]
parameter=valueM
```

All parameters are optional, unless directly stated that they are required.

Parameter	Data Type	Description	Default
<i>gender</i>	ushort	Gender flag (0=male, 1=female).	0
<i>pic</i>	ushort	Index of the main (default) picture.	0
<i>picdead</i>	ushort	Index of the death picture (displayed when hero is dead).	0
<i>picfrozen</i>	ushort	Index of the frozen picture (displayed when hero becomes frozen by a spell etc.).	0

## Encounter definitions

Encounter definitions specify random monster encounters that may happen to the hero while they are traveling through the wilderness. Encounters only apply to random locations in the wilderness. They have no effect on monsters encountered in the underground locations or any kind of predefined locations.

They are stored in `enc.XX.ini`. The file has the following format:

```
[header]
encounters=N

[enc0]
parameter=value1
```

[enc1]  
parameter=value2

...

[encN-1]  
parameter=valueM

All parameters are optional, unless directly stated that they are required.

<b>Parameter</b>	<b>Data Type</b>	<b>Description</b>	<b>Default</b>
<i>EncounterText</i>	string	A text message that is displayed when the hero triggers the encounter.	0
<i>InternalText</i>	string	An internal text message. It is not displayed in the game, but might be used by development tools (e. g. in the editor) or in the code.	0
<i>DifficultyLevel</i>	float	The encounter may happen only if the difficulty level for it matches the difficulty level of the location (i. e. it's not greater than the location level and not significantly lower than it).	1.0
<i>MetaData</i>	string	Various additional data (see below).	(empty string)
<i>MonTypeX*</i>	ushort	Identifies monster (or NPC) to be encountered.	0
<i>MonNumLowX*</i>	ushort	Specifies number of monster instances to be created. The actual number is a random integer from the range ( <i>MonNumLowX</i> , <i>MonNumberHighX</i> ).	0**
<i>MonNumberHighX*</i>	ushort	See above.	0**
<i>ScriptX*</i>	string	Script file to be used if the creature to be encountered is a NPC. Ignored for monsters.	(empty string)

\* Where X is a consecutive integer number (1, 2, 3 and so on).

\*\* The default value is 1 if X is greater than 1.

The value of *MetaData* defines the behavior of encountered creatures. Possible values are:

- *neutral* – creatures does not attack the player (unless in self-defence)
- *hostile* – creatures attack the player immediately

To create a battle encounter (i.e. one group of creatures fighting another group), you must place at least one monster type with *MetaData* equal to *attackers* and at least one with *MetaData* equal to *defenders*. These values do not combine with *neutral* or *hostile*.